Claims Pending

1.(cancelled)

2.(cancelled)

3.(cancelled)

4.(cancelled)

5.(cancelled)

6.(cancelled)

7.(cancelled)

8.(cancelled)

9.(cancelled)

1   10.(presently amended)   A railroad grade crossing assembly for

2   blocking access across a railroad crossing, comprising:

3   gate means connectable to a stanchion and movable between a

4   generally upright position to permit access across the railroad

5   crossing and a generally horizontal position for blocking access

6   across the railroad crossing; and

7   telescopic arm means incorporated into said gate means for

8   automatically closing and opening the railroad crossing in response

9   to a signal, said telescopic arm means being movably incorporated

10 within said gate means and being selectively operable according to

11 said signal to extend from said gate means each time said crossing

12 assembly is to block access across said crossing and retracts

13 according to said signal each time said crossing assembly is to

14 permit access across said crossing; and

15   programmable electronic means responsive to at least one of

16   selective gate operating parameters, and

2

17   selective electrical signals,

18 and provides in response thereto at least one output signal in

19 response thereto to said gate means to programmably control at

20 least one of

21   a first gate position motion initiation in response to a

22 second gate position,

23   a gate position duration,

24   a communication of diagnostic data,

25   a communication of video data,

26   an initiation of a failure condition, and

27   the reception of electronic controller programming data.

1 11.(original) A railroad grade crossing assembly as recited in

2 claim 10, further comprising a wireless link that is coupled to

3 said programmable electronic means and is operable to receive

4 programming instructions for implementation by said programmable

5 electronic means.

1 12.(original) A railroad grade crossing assembly as recited in

2 claim 10, wherein said programmable electronic means comprises a

3 programmable logic controller coupled to one or more relays.

1 13.(previously amended) A railroad grade crossing assembly as

2 recited in claim 10, further comprising means for electronically

3 monitoring at least one of usage and status of the assembly.

1   14.(original) A railroad grade crossing assembly as recited in

2   claim 13, further comprising a wireless link that is coupled to

3   said means for electronically monitoring and is operable to receive

4   data from said means for electronically monitoring.

1   15.(original) A railroad grade crossing assembly as recited in

2   claim 13, further comprising a wireless link that is coupled to

3   said means for electronically monitoring and is operable to

4   transmit data generated by said means for electronically monitoring

5   to a remote monitoring station.

1   16.(previously amended) A railroad grade crossing assembly as

2   recited in claim 13, further comprising one or more cameras for

3   visually monitoring at least one of the assembly and the area

4   around assembly.

1   17.(previously amended) A railroad grade crossing assembly as

2   recited in claim 10, wherein at least one of said gate means and

3   said telescopic arm means includes lights that incorporate a

4   bulletproof material.

1   18.(previously amended) A railroad grade crossing assembly as

2   recited in claim 10, wherein at least one of said gate means and

3   said telescopic arm means includes lights and a bulletproof

4   covering for protecting said lights.

1   19.(original) A railroad grade crossing assembly as recited in

2   claim 10, further comprising an electric motor for extending and

3   retracting said telescopic arm means, and wherein said programmable

4   electronic means is operable to control said motor.

1   20.(original) A railroad grade crossing assembly as recited in

2   claim 19, wherein said motor is coupled to said telescopic arm

3   means through a clutch that is released upon failure of said

4   motor's power supply.